

Mercury Series Engines



LP428G2

LP428G2 Engine

fixed speeds
1500 r/min

29 – 32 kWm | 38.9 – 42.9 bhp²



OVER VIEW

The engine is specifically designed as a Power generating engine suitable for use in Stage II emissions territories. It is durable, reliable and easy to maintain with oil & filter changes up to 500 hours, dependant on operational conditions. It is designed for continuous operation in ambient temperatures up to 52°C (125°F) and a cold start capability down to -25°C (-13°F).

G Build

Note:

This engine does not comply with Harmonised International Regulated Emissions Limits.

For further information and approval please contact Applications Department

* Optional items standard on most builds.

BASIC ENGINE CHARACTERISTICS

- direct fuel injection
- 4 cylinders
- liquid cooled
- Turbocharged aspirated

DESIGN FEATURES AND EQUIPMENT

- electric starting
- anti clockwise rotation, looking on the flywheel end
- SAE Flywheel connection
- SAE compliant flywheel housing
- radiator and fan guard
- cast-iron structural crankcase
- self-vent fuel injection system
- mechanical fuel injection equipment
- mechanical and electronic governing variants
- flywheel and gear ring
- cyclonic heavy duty airfiltration
- oil pressure protection switch
- coolant temperature protection switch
- spin-on full flow lubricating oil filter
- fuel filter / agglomerator
- intake and exhaust manifolds
- operators' handbook

OPTIONAL ITEMS

A range of options are available that allows you to select a specification that matches your requirements; please consult your Lister Petter Engine distributor.

POWER OUTPUTS³ | Stage II EMISSIONS RATINGS

Model	Speed, r/min	Power	Gross ²		Net		Standard Generator Output*		
			kW	bhp	kW	bhp	Power	kVA	kWe
LP428G2	1500	Continuous	29	38.9	28	37.5	PRP	30	24
		Fuel Stop	32	42.9	31	41.5	ESP	33	26

TECHNICAL DATA

Engine fixed speed 1500r/min		LP428G2
Type of fuel injection		Direct
Number of cylinders		4
Aspiration		Turbocharged aspirated
Direction of rotation (flywheel end)		Anti clockwise
Nominal cylinder bore	mm	93
	in	3.7
Stroke	mm	102
	in	4.0
Total cylinder capacity	litre	2.8
	in ³	170.9
Compression ratio		18.2:1
Firing order (number 1 cylinder is at the gear end)		1-3-4-2
Alternator		12V×50A
Starter motor		12V×3kW
Fuel injection pump		Mechanical
Speed governor		Mechanical/Electronic
Speed regulation class		ISO 8528 G3
Fly wheel housing		SAE 4
Fly wheel		SAE J620 Size 7.5"

RATING DEFINITIONS TO ISO 3046**ISO Standard Conditions**

Barometric pressure 100kPa
Relative humidity 30%
Ambient air temperature at the inlet manifold 25°C

Power Standards

The engine performance corresponds to ISO 3046, BS 5514 and DIN 6271. The technical data applies to an engine without cooling fan and operating on a fuel with calorific value of 42.7 MJ/kg (18360 BTU/lb) and a density of 0.84 kg/liter (7.01 lb/US gal, 8.42 lb/Imp gal).

Fixed Speed: Continuous Power (ICN)

The power in kW which the engine is capable of delivering continuously at the stated crankshaft speed, under ISO 3046 standard conditions, measured at the flywheel without power-absorbing accessories, provided that the engine is overhauled and maintained in good operating condition and that fuel to BS EN 590 Class A1 or A2, and lubricating oils to the correct performance specification and viscosity classification as recommended by Lister Petter Engine Company are used.

Fixed Speed (Fuel Stop): Overload Power (ICXN)

The maximum power in kW which the engine is capable of delivering intermittently at the stated crankshaft speed for a period not exceeding one hour in any period of twelve hours of continuous running, immediately after working at the continuous power, under ISO 3046 standard conditions and with the provisions specified for continuous power in item (1) above, but with the fuel limited so that the fuel stop power cannot be exceeded.

Derating

For non-standard site conditions, reference should be made to relevant BS, ISO & DIN standards.

Notes:

1. Power ratings are measured at the flywheel end.
- 2.. Power ratings and fuel consumption figures apply to a fully run-in, non derated engine without a radiator and fan fitted, and without power absorbing accessories or transmission equipment.

* The power output of the generator data is calculated using a figure of 86% efficiency of the AC generator. The kVA and kWe values are converted as per standard power factor 0.8. Generator data is for reference only.

EXHAUST AND INTAKE SYSTEM | 1500 RPM FIXED SPEED ENGINES

Parameter	Engine Model
	LP428G2
EXHAUST	
Maximum allowable back-pressure (kPa)	≤ 7.1
Exhaust gas flow, (m ³ /min)	6.8
Emissions level	Stage II
Exhaust gas temperature, continuous (°C)	330
Exhaust gas temperature, overload (°C)	380
Exhaust pipe diameter -recommended	63mm
INTAKE	
Maximum allowable inlet restriction (kPa)	≤ 2.1
Combustion air flow(m ³ /min)	3.2

ENGINE COOLANT SYSTEM | 1500 RPM, FIXED SPEED

Parameter	Engine Model
	LP428G2
Cooling method	Liquid cooled (belt driven water pump)
RADIATOR	
Material	Aluminium
Radiator face area (m ²)	11
Pressure cap setting (kPa)	90
FAN	
Diameter (mm)	420
Number of blades	7
Material	Plastic
Type	Blower type
COOLANT	
Cooling package maximum operating temperature (°C)	≤104
Total system with radiator capacity (L)	10.5
Total system without radiator capacity (L)	4
Thermostat type	Wax Capsule
Thermostat opens at... (°C)	82
Thermostat fully open at... (°C)	≤ 95
Minimum temperature to engine (°C)	-25
Maximum static pressure head at pump (meters at 1500rpm)	14
Cooling fan flow rate (m ³ /s)	2.3

Recommended coolant:

50% ethylene glycol with a corrosion inhibitor (BS 6580 : 1992 or ASTM D3306-89 or AS2108) and 50% de-ionised water

ENGINE LUBRICATION SYSTEM

Parameter	Engine Model
	LP428G2
Lubricating method	Pressure feed and splash
Sump capacity including filter (L)	5.6
Service Interval (hr)	500
Oil filter type	Spin-on full flow oil filter
Oil Specification	API CH-4
	ACEA E5
Oil consumption % SFC	≤ 0.1%
Oil consumption, 100% (l/hr)	0.06
Lubricating oil temperature (°C)	90-105
Maximum oil temperature (°C)	108
Maximum operation angle of engine (degrees)	10°

APPROXIMATE FUEL CONSUMPTION

Speed, r/min	Load	Engine model	
		LP428G2	
		g/kWh	l/h
1500	110%	233	9.3
	100%	221	8
	75%	239	6.5
	50%	248	4.5
	25%	254	2.3

*Diesel fuel density 0.835 g/ cm³


* The power output of the engine is calculated according to NPT conditions.

* For non-standard site conditions not listed, reference should be made to BS, ISO and DIN standards.

ENGINE NOISE LEVELS

Parameter	Engine Model
	LP428G2
Sound pressure level at 1m	≤95 dB(A)

APPROXIMATE DIMENSIONS AND WEIGHT



Engine model		LP428G2
Dry weight	kg	240
	lb	528
Length (A)	mm	750
	in	29.3
Width (B)	mm	615
	in	24.0
Height (C)	mm	693
	in	27.0



Head Office
Lister Petter Engine Company

Distributor Address